

### Material

illbruck TN133 is polyethylene based filler cord with predominantly closed cells.

### Packaging

PE cord wound into a roll.

Available diameters ; 8; 10; 15; 20; 25; 30; 40; 50 mm

Length in a roll: 100m - Ø6-15 mm; 50 m - Ø20-30 mm; 30 m - Ø30-50 mm

### Technical data

Property	Results
Compression set	65 %
Thermal conductivity	0, 044 W/ m . K
Temperature resistance	- 80 °C to +100 °C
Application temperature	no limits
Shelf life	no limits
Storage temperature	+ 5°C to +25°C

### Surface preparation

1. The substrate surface must be dry, degreased, and free of dust and loose particles, which could negatively affect the adhesion.

### Processing

1. It is always necessary to choose a bigger cord diameter than is the width of sealing joint. Press the cord between fingers and push it gradually into the joint. Joint be immediately sealed.

### Tips and Tricks

1. PE cord is ideal filling material under silicones, hybride and polyurethane sealants and adhesives. Material does not contain any amount of silicone. It can be used in paintshops without restriction.



## TN133

### PE Cord



#### Description

It serves mainly as ideal base material under different kind of mastics. It prevents the unwanted adhesion of the sealant to the bottom side of the joint.

#### Benefits

- Clean to use
- Suitable for indoor and outdoor
- No adhesive

**Technical service**

tremco illbruck has a team of experienced Technical Service Representatives who provide assistance in the selection and specification of products. For more detailed information, service and advice, please call Customer Service.

**Warranty**

tremco illbruck products are manufactured to rigid standards of quality. Any product which has been applied (a) in accordance with tremco

illbruck written instructions and (b) in any application recommended by tremco illbruck, but which is proved to be defective, will be replaced free of charge.;No liability can be accepted for the information provided in this leaflet although it is published in good faith and believed to be correct.;tremco illbruck Ltd. reserves the right to alter product specifications without prior notice, in line with Company policy of continuous development and improvement.



**tremco illbruck s.r.o.**  
Slezská 2526/113  
13000 Praha 3  
Česká republika  
T: +420 296 565 381  
F: +420 296 565 300

prodej@tremco-illbruck.com  
www.tremco-illbruck.cz